Transparent Botnet Command and Control for Smartphones over Text Messages

Georgia Weidman

Why Smartphone Botnets

Ubiquitous smartphones

Common development platforms

Strong technical specs

Why Text Messages?

Battery managements

Difficult to monitor

Fault Tolerant


Telephony Stack (Userspace)


Serial Line/ Modem Driver


Telephony Stack (Userspace)


Serial Line/ Modem Driver


Modem




















At Blackhat 2009, Charlie Miller & Collin Mulliner proxied the application layer and modem to crash smartphones with SMS.

http://www.blackhat.com/presentations/bh-usa-09/MILLER/BHUSA09-Miller-FuzzingPhone-PAPER.pdf

Telephony Stack (Userspace)

Serial Line/ Modem Driver

Telephony Stack (Userspace)

Injector

Serial Line/ Modem Driver

Telephony Stack (Userspace)

Injector

Serial Line/ Modem Driver

My Work: SMS Botnet C&C

Telephony Stack (Userspace)

Injector

Serial Line/ Modem Driver

My Work: SMS Botnet C&C

Telephony Stack (Userspace)

BOT

Serial Line/ Modem Driver

SMS-Deliver PDU

07914140540510F1040B916117345476F100000121037140044A0A

E8329BFD4697D9EC37

Field	Value
Length of SMSC	07
Type of Address (SMSC)	91
Service Center Address (SMSC)	41 40 54 05 10 F1
SMS Deliver Info	04
Length of Sender Number	0B
Type of Sender Number	91
Sender Number	51 17 34 45 88 F1
Protocol Identifier	00
Data Coding Scheme	00
Time Stamp	01 21 03 71 40 04 4A
User Data Length	0A
User Data	E8 32 9B FD 46 97 D9 EC 37

SMS-Deliver PDU

07914140540510F1040B916117345476F100000121037140044A0A

E8329BFD4697D9EC37

User Data Length User Data	OA E8 32 9B FD 46 97 D9 EC 37
Time Stamp	01 21 03 71 40 04 4A
Data Coding Scheme	00
Protocol Identifier	00
Sender Number	61 17 34 54 76 F1
Type of Sender Number	91
Length of Sender Number	0B
SMS Deliver Info	04
Service Center Address (SMSC)	41 40 54 05 10 F1
Type of Address (SMSC)	91
Length of SMSC	07
Field	Value

1. Bot Receives Message

2. Bot Decodes User Data

3. Bot Checks for Bot Key

1. Bot Receives Message

2. Bot Decodes User Data

3. Bot Checks for Bot Key

1. Bot Receives Message

2. Bot Decodes User Data

3. Bot Checks for Bot Key

1. Bot Receives Message

2. Bot Decodes User Data


3. Bot Checks for Bot Key

1. Bot Receives Message


2. Bot Decodes User Data

3. Bot Checks for Bot Key


Botnet Structure




Master Bot



Sentinel Bots



Slave Bots



Security Concerns

Impersonation

Replay

Cryptographic solutions

Limitations

Possible detection methods

User data length

Getting the Bot Installed

Regular Users

Rooted/Jailbroken Users

Remote

Example Payloads

Spam

Denial of service

Load new functionality

Degrading cell service

What This Really Means

 If attackers can get the bot installed they can remotely control a user's phone without giving any sign of compromise to the user.

Mitigations

Integrity checks

Liability for smartphone applications

User awareness

Demo

Android Bot with Spam Payload

Contact

- Georgia Weidman
- Company: Neohapsis Inc.
- •Email: Georgia@grmn00bs.com

Georgia.weidman@neohapsis.com

- •Website: http://www.grmn00bs.com
- Twitter: vincentkadmon

Selected Bibliography

•SMS fuzzing:

http://www.blackhat.com/presentations/bh-usa-09/MILLER/BHUSA09-Miller-FuzzingPhone-PAPER.pdf

•Cell bots attack GSM core:

http://www.patrickmcdaniel.org/pubs/ccs09b.pdf

•Twilight botnet:

http://jon.oberheide.org/files/summercon10-androidhax-jonoberheide.pdf

•SMS/P2P iPhone bots:

http://mulliner.org/collin/academic/publications/ibots_malware10_mulliner_seifert.pdf